

VC Type Chain Block



Features:

- Adopt Japanese technology, which is the convex word process.
- Low-alloy steel, which is reliable and durable.
- Premium alloy steel grade 80 load chain, which is safe and long serving life.
- Smooth operation, high efficient, small hand pulling force.
- Double pawls, two load chain guides wheel, which are safer.
- Needle bearing optioned.
- Widely used in the nuclear power station, thermal power station, etc.



Moving




Pull out the tree




Lifting pump




The pipes





0.5-2t



3-5t



7.5t-10t-15t



20t

Model	Capacity (t)	Standard Lift (m)	Test Load (t)	Effort required to lift max load(N)	No.of falls of load chain	Load chain diameter (mm)	Dimension(mm)				Net Weight (kg)
							A	B	H	D	
VC00525	0.5	2.5	0.75	350	1	5	126	145	285	28	11
VC01003	1	3	1.5	330	1	6.3	151	159	315	32	12.5
VC01503	1.5	3	2.25	348	1	7.1	151	178	340	36	17.8
VC02003	2	3	3	365	1	8	183	205	380	36	19.5
VC03003	3	3	4.5	360	2	7.1	151	208	475	46	29
VC05003	5	3	7.5	410	2	9	183	264	600	46	23.5
VC10003	10	3	15	410	4	9	188	398	720	57	41.3
VC15003	15	3	22.5	435	6	9	190	580	870	75	78.5
VC20003	20	3	30	435*2	8	9	192	630	890	82	193
VC30003	30	3	45	435*2	12	9	330	670	1000	106	220

• Note:We reserve the right to change parameters without prior notification.